

## Features

### Automatic CDBC Coffee Brewers

- Larger 200 oz. tank provides back-to-back brewing capacity.
- Convertible by flipping a switch to 120V/15 amp. or 208-240V/20 amp.
- Improved brewing system has better temperature accuracy.
- Quicker install saves up to 30 minutes. Pot level, cold brew lock-out and tank temperature set easily from advanced touch pad on front of machine.
- Faster field repairs and quick problem diagnostics by phone; built-in electronic sensors feed back information on brewer malfunctions.
- SplashGard® funnel deflects hot liquids away from the hand.
- Coffee extraction controlled with pre-infusion, Pulse Brew™ and digital temperature control.



*Model CDBCF-DV  
(2 top warmers)  
(decanters not included)*

Dimensions: 18.9" H x 8.25" W x 17.8" D

## CDBC Product Line

For current specification sheets and other information, go to [www.bunnomatic.com](http://www.bunnomatic.com).

BUNN recommends the use of our Easy Clear® Water Quality Systems and BUNN paper filters to assure perfect taste.

**Easy Clear® EQ-17-TL**  
Product No. : 30200.1000  
Dimensions:  
12<sup>7</sup>/<sub>16</sub>" H x 2<sup>1</sup>/<sub>2</sub>" W x 3" D



**Easy Clear® ED-17-TL**  
Product No. : 30201.1001  
Dimensions: 8<sup>1</sup>/<sub>4</sub>" H x 2<sup>5</sup>/<sub>16</sub>" Dia.

**Paper Filter Pack**  
Product No. : 20115.0000  
Packed per case: 1,000  
Dimensions: 4<sup>1</sup>/<sub>4</sub>" Base x 2<sup>3</sup>/<sub>4</sub>" Sidewall



**Easy Pour® black decanter**  
Product No. : 06100.0101  
Quantity: 1 (also packaged in quantities of 2, 3, 6, 12, & 24)



**1GPR SS Portable Server on an RWS1 Warmer**  
1GPR Product No. : 12487.0001\*  
RWS1 Product No. : 12203.0010  
*\*Also available with side handles or black decor.*



ITEM#

PROJECT

DATE

## Model

*CDBCF-DV*

## BUNN®

**Corporate Offices**  
1400 Stevenson Drive  
Springfield, Illinois 62703  
**Phone**  
800-637-8606  
217-529-6601  
**Fax**  
217-529-6644  
**Technical Services**  
800-286-6070  
**Internet**  
<http://www.bunnomatic.com>

**Western Regional Office**  
16431 Carmenita Road,  
Cerritos, California 90701  
**Phone**  
562-926-0764  
**Fax**  
562-926-0858

**Canadian Office**  
280 Industrial Parkway South  
Aurora, Ontario, L4G 3T9  
**Phone**  
905-841-2866  
**Fax**  
905-841-2775

Patents  
Apply



## Dimensions & Specifications

Model	Product #	Volts	Amps	Tank Heater Watts	Total Watts	Brewing Capacity	Cu. Ft.	Shipping Weight	Cord Attached
CDBCF-DV (2 top)	28800.0230	120 <sup>†</sup>	15	1425	1800	4.5 gal./hr.	4.0	27 lbs. (12.3 kg)	No
CDBCF-DV (2 top)*	28800.0231	120 <sup>†</sup>	15	1425	1800	4.5 gal./hr.	4.0	27 lbs. (12.3 kg)	No
		208	20	2390	2752	6.8 gal./hr.			
		240	20	3180	3534	6.8 gal./hr.			

<sup>†</sup>Model also switchable to these electrical configurations

\*Model has a stainless steel funnel.

**Electrical:** 120 volt, 15 amp. models require 2-wires plus ground service rated 120V, single phase, 60 Hz. An internal terminal block is configured for connection to a 3-wire plus ground.

**Plumbing:** 20-90 psi (138-621 kPa). Machines supplied with 1/4" male flare fitting. Twin models supplied with 3/8" male flare fitting.

