

### Features

#### 12 Cup Automatic Coffee Brewer

- Brews 3.8 to 6.8 gallons of perfect coffee per hour.
- Model is space-saving 8" wide.
- All stainless steel construction.
- Hot water faucet and pourover feature on all models.
- SplashGard® funnel deflects hot liquids away from the hand.
- International electrical configurations available.



Model CWTF15-3\*  
(2 top warmers)

(decanters not included)

Dimensions: 18.9" H x 8.25" W x 17.8" D

\* International models may vary in appearance.

### Related Products

For current specification sheets and other information, go to [www.bunnomatic.com](http://www.bunnomatic.com).

BUNN recommends the use of our Easy Clear® Water Quality Systems and BUNN paper filters to assure perfect taste.

#### Easy Clear® EQ-17-TL

Product No. : 30200.1000

Dimensions:

12<sup>7</sup>/<sub>16</sub>" H x 2<sup>1</sup>/<sub>2</sub>" W x 3" D

31.6 cm H x 6.35 cm W x 7.62 cm D

#### Easy Clear® ED-17-TL

Product No. : 30201.1001

Dimensions: 8<sup>1</sup>/<sub>4</sub>" H x 2<sup>5</sup>/<sub>16</sub>" Dia.

20.95 cm H x 5.87 cm Dia.



#### Paper Filter Pack

Product No. : 20115.0000

Packed per case: 1,000

Dimensions: 4<sup>1</sup>/<sub>4</sub>" Base x 2<sup>3</sup>/<sub>4</sub>" Sidewall

10.8 cm Base x 6.98 cm Sidewall



#### Easy Pour® black decanter

Product No. : 06100.0101

Quantity: 1 (also packaged in quantities of 2, 3, 6, 12, & 24)



#### 1GPR SS Portable Server on an RWS1 Warmer

1GPR Product No. : 12487.0001\*

RWS1 Product No. : 12203.0010

\*Also available with side handles or black decor:



BUNN® practices continuous product research and improvement. We reserve the right to change specifications and product design without notice. Such revisions do not entitle the buyer to corresponding changes, improvements, additions or replacements for previously purchased equipment.

ITEM#

PROJECT

DATE

### International Model

CWTF A20

CWTF A35

### Model

CWTF15-3

CWTF20-3

CWTF35-3

## BUNN®

#### Corporate Offices

1400 Stevenson Drive  
Springfield, Illinois 62703

**Phone**

800-637-8606

217-529-6601

**Fax**

217-529-6644

**Technical Services**

800-286-6070

**Internet**

<http://www.bunnomatic.com>

#### Western Regional Office

16431 Carmenita Road,  
Cerritos, California 90701

**Phone**

562-926-0764

**Fax**

562-926-0858

#### Canadian Office

280 Industrial Parkway South  
Aurora, Ontario, L4G 3T9

**Phone**

905-841-2866

**Fax**

905-841-2775

Patents  
Apply



## Dimensions & Specifications

Model	Product #	Volts	Amps	Tank Heater Watts	Total Watts	Brewing Capacity	Cu. Ft.	Shipping Weight	Cord Attached
CWTF15-2	12950.0211	120	15	1320	1800	3.8 gal./hr.	3.85	30 lbs. (13.6 kg)	Yes
CWTF15-3	12950.0213	120	15	1320	1800	3.8 gal./hr.	3.85	31 lbs. (14.1 kg)	Yes
CWTF15-3	12950.0217	120	15	1320	1800	3.8 gal./hr.	3.85	32 lbs. (14.5 kg)	Yes
CWTF20-3	12950.0283	120	20	1800	2400	5.1 gal./hr.	3.98	31 lbs. (14.1 kg)	No
CWTF35-3	12950.0253	120/240	19.6	3500	4100	6.8 gal./hr.	3.9	30 lbs. (13.6 kg)	No
CWTF35-3	12950.0261	120/240	19.6	3500	4100	6.8 gal./hr.	3.85	32 lbs. (14.5 kg)	No

Electrical: Model 15 requires 2-wires plus ground service rated 120V, single phase, 60 Hz.

Model 20 requires 2-wires plus ground service rated 120V, single phase, 60 Hz.

Model 35 requires 3-wires plus ground service rated 120/208 or 120/240V, single phase, 60 Hz.

Plumbing: 20-90 psi (138-621 kPa). Machine supplied with 1/4" male flare fitting.

