

### Features

#### 10 Cup Home Pourover Coffee Brewer

- Original hot water reservoir-style home brewers.
- Brews 10 cups of perfect coffee in just 3 minutes.
- Hot water always available.
- Stainless steel tank.
- Separately controlled warmer.
- Advanced sprayhead design.
- Brewing system thermostat.
- Vacation switch.
- Deliver quality coffee brewed to the exacting standards of fine restaurants worldwide.
- High altitude models available.



Model GR10-B



Model GR10-W



### Related Products

For current specification sheets and other information, go to [www.bunnomatic.com](http://www.bunnomatic.com).

#### BUNN Paper Filters

Box of 1000  
Product No.: 20106.0000



#### NCD decanter

Product No. :  
20424.0006  
(10 cups/50 oz.)



#### Auxillary warmer

Product No. : 04875.0001



*All accessories available online at [www.bunnomatic.com](http://www.bunnomatic.com)*

BUNN® practices continuous product research and improvement. We reserve the right to change specifications and product design without notice. Such revisions do not entitle the buyer to corresponding changes, improvements, additions or replacements for previously purchased equipment.



### Model

GR10-B  
# 33300.0034

GR10-W  
# 33300.0032

## BUNN®

**Corporate Offices**  
1400 Stevenson Drive  
Springfield, Illinois 62703  
**Phone**  
800-352-2866  
217-529-6601  
**Fax**  
217-585-7808  
**Internet**  
[www.bunnomatic.com](http://www.bunnomatic.com)

**Western Regional Office**  
16431 Carmenita Road,  
Cerritos, California 90701  
**Phone**  
562-926-0764  
**Fax**  
562-926-0858

Household Use Only  Patents Apply

## Dimensions & Specifications

Model	Product #	Volts	Amps	Tank Heater Watts	Total Watts	Decanter Capacity	Brewing Speed	Shipping Weight
GR10-B	33300.0034	120	7.5	800	900	50 oz. (10 cups)	3 minutes	8 lbs. (4.5 kg)
GR10-W	33300.0032	120	7.5	800	900	50 oz. (10 cups)	3 minutes	8 lbs. (4.5 kg)

*Both brewers come with 10 cup (50 oz.) decanter, coffee funnel, delimiting spring & filters.*

Electrical: Model has attached cordset and requires 2-wire grounded service rated 120V, single phase, 60 Hz.

